

Certainty in a connected world

APC Back-UPSTM 650

Power and protect your critical electronics from damage due to power outages, surges and spikes while providing short term battery power during an outage. The Back-UPS 650 protects your equipment and network connection in harsh power environments, ensuring maximum productivity while maintaining work efficiency.

www.apc.com





APC Back-UPSTM



Power and protect your critical electronics from damage due to power outages, surges and spikes while providing short term battery power during an outage. The Back-UPS 650 protects your equipment and network connection in harsh power environments, ensuring maximum productivity while maintaining work efficiency.

Certainty in a connected world

The new APC Back-UPS 650 combines high value features with affordable pricing.

4 Schuko "Battery Backup & Surge Protected" Sockets

Power and protect your critical electronics equipment that require battery back-up along with surge protection allowing you to save your work and protect your data when the power goes out or fluctuates at dangerous levels.

Push Button Circuit Breaker

Easily recover from circuit overloads and protect your fuse box and electronics from electrical damage.

LED Indicator and Audible Alarms

Quickly understand your UPS unit and power status through visual and audible indicators.

2 Year Warranty

APC assures customer peace of mind offering a 2 year warranty with free technical phone and online support.



APC Back-UPS 650 Applications

- PC and Peripherals
- Networking equipment (router, modem)
- Network Attached Storage (NAS)
- Game console
- Projector with impulse power
- Landline cordless phone





APC Back-UPS

BC650-RSX761 Technical Specifications

Output	
Output Capacity	650VA / 360 Watts
Output Voltage / Frequency (On utility)	230V / 50/60 +/- 1Hz
Output Voltage / Frequency (On battery)	230V +/- 8% 50 or 60 Hz +/- 1Hz (auto-sensing)
Output Connections	4 Schuko sockets All with battery backup and surge protection
Waveform Type	Stepped Approximation to Sine Wave
Input	
Maximum Adjustable Input Voltage / Frequency	160 - 278 V / 45 ~ 65 Hz (50, 60 Hz auto-sensing)
Input Over Current Protection	7A Circuit Breaker
Surge Protection	-
AC Power Surge Protection	All Sockets
Physical	-
Unit Dimensions (H x W x D)	200 x 115 x 256 mm
Unit Weight	5.5 Kg
Shipping Dimensions (H x W x D)	343.5 x 200 x 278.5 mm
Shipping Weight	6.2 Kg
Color	Black
UPC Code	731304326311
Battery	
Battery Type	Maintenance-free, sealed lead-acid battery, leak proof
Typical Recharge Time	8 hrs
Management	
Alarms	Visual (LED) and audible alarms
Adjustable Sensitivity and Transfer Voltage	Low, Medium (default), High

