

Product datasheet

Specifications



APC SMART-UPS SRT LI-ION 3000VA RM 230V NETWORK CARD

SRTL3000RMXLI-NC

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead Time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	2700 W
Rated Power In Va	3000 VA
Input Connection Type	IEC 60320 C20
Output Connection Type	6 IEC 60320 C13 2 IEC 60320 C19
Number Of Rack Unit	3U
Cable Length	1.83 m
Number Of Cables	1
Provided Equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card

Batteries & Runtime

Run Time	View Runtime Graph
Battery Type	Li-Ion (Lithium-Ion)
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	4 h
Battery Voltage	48 V
Battery Charger Power	158 W rated
Battery Life	5...10 year(s)
Extended Runtime	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

General

Ups Type	Double conversion online
Product Web Sub-Family	Lithium-Ion
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Black with silver front bezel
Height	12.8 cm
Width	43.2 cm
Depth	63.9 cm
Net Weight	30.5 kg
Mounting Preference	No preference
Mounting Mode	Rack-mounted with kit
Two Post Mountable	0
Usb Compatible	Yes
Mounting Position	Horizontal Vertical

Input

Network Frequency	40...70 Hz auto-sensing
Input Voltage Limits	160...275 V

Output

Maximum Configurable Power In Va	3000 VA
Maximum Configurable Power In W	2700 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains
Wave Type	Sine wave
Harmonic Distortion	Less than 2 %
Crest Factor	3 : 1
Bypass Type	Built-in bypass

Conformance

Product Certifications	CE EAC
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	0...40 °C
---------------------------------------	-----------

Relative Humidity	0...95 % non-condensing
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0.00...15240.00 m
Acoustic Level	50 dBA
Heat Dissipation	317 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Free Slots	0
Preinstalled Device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off	Yes

Surge Protection and Filtering

Surge Energy Rate	432 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	87 cm
Package 1 Length	60 cm
Package 1 Weight	41.4 kg

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Sustainability



Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performances. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

- ✓

 Energy Efficient Product
- ✓

 Take-Back Program Available

Well-being performance

- ✓

 Mercury Free
- ✓

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information