Product datasheet

Specification





APC Symmetra LX 16kVA Scalable to 16kVA N+1 Rackmount, 220/230/240V or 380/400/415V

SYA16K16RMI

Overview

Presentation	High performance, redundant power protection with scalable power and runtime for space-constrained server rooms, and voice and data networks.
Lead Time	Usually in Stock
Main	
Main Input Voltage	230 V 400 V 3 phases
Other Input Voltage	220 V 240 V 380 V 415 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	11200 W
Rated Power In Va	16000 VA
Output Connection Type	8 IEC 60320 C13 10 IEC 60320 C19
Output Connector Type	Hard wire 3-wire (H N + E) 1
Number Of Rack Unit	19U
Battery Type	Lead-acid battery
Provided Equipment	CD with software Documentation CD Installation guide User manual Web/SNMP management card

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number Of Battery Filled Slots	4
Number Of Battery Free Slots	0
Battery Recharge Time	3 h
Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
Battery Charger Power	1148 W rated
Battery Life	35 year(s)
Extended Runtime	1



General

Product Web Sub-Family	4kVA power increments
Number Of Power Module Free Slots	1
Number Of Power Module Filled Slots	4
Redundant	Yes

Physical

Colour	Black Silver
Height	83.8 cm
Width	47.2 cm
Depth	68.8 cm
Net Weight	286.82 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	4565 Hz auto-sensing
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	155276 V 290480 V 3:1
Input Harmonic Distortion	Less than 7 % for full load
Input Power Factor At Full Load	0.98

Output

Maximum Configurable Power In W	11200 W
Harmonic Distortion	Less than 5 % at full load
Output Frequency	4763 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest Factor	Up to 5 : 1
Ups Type	Double conversion online
Wave Type	Sine wave
Bypass Type	Internal bypass (automatic and manual)
Maximum Output Current	73 A
Maximum Configurable Power In	16000 VA

Conformance

Product Certifications	C-Tick CE GOST VDE	
Standards	EN 50091-1 EN 50091-2	
	EN 55022 class A	
	EN 55024	
	EN 60950	
	IEC 60950	

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-1545 °C
Storage Relative Humidity	095 %
Storage Altitude	0.004572.00 m
Acoustic Level	62 dBA
Heat Dissipation	3707 Btu/h

Communications & Management

Free Slots	1
Preinstalled Device	Network management card 2 with environmental monitoring
Control Panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off	Yes

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	105.4 cm
Package 1 Width	59.9 cm
Package 1 Length	99.7 cm
Package 1 Weight	340.45 kg

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performances. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Learn more about Green Premium >







Energy Efficient Take-back RoHS/REACh

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation REACh Declaration Compliant with Exemptions **Eu Rohs Directive China Rohs Regulation** China RoHS declaration Product out of China RoHS scope. Substance declaration for your information The product must be disposed on European Union markets following specific waste Weee collection and never end up in rubbish bins