Product datasheet

Specifications





Easy Rack PDU, Switched, 0U, 3 Phase, 22kW, 230V, 32A, 18 C13 and 6 C19 outlets, IEC60309 3P + N + PE inlet

EPDU1232S

			~
		\/	$-\infty$
\smile	\sim 1	V 1	ew

Lead Time Usually in Stock

Main

Colour	Black
Pdu Type	Switched

Complementary

Input Voltage	400 V 3 phases
Height	1794 mm
Width	55 mm
Output Voltage	230 V
Depth	62 mm
Net Weight	8.17 kg
Mounting Location	Side
Input Plug Type	IEC 60309 32 A 3P + N + PE
Mounting Position	Vertical
Input Current Limits	32 A
Load Capacity	22 kW
Network Frequency	50/60 Hz
Plug Standard	IEC 60309
Outlet Type And Quantity	18 IEC 60320 C13 6 IEC 60320 C19

Environment

Product Certifications	CE EAC RCM TÜV
Ambient Air Temperature For Operation	-545 °C
Relative Humidity	595 %
Operating Altitude	03000 m
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	595 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1950 mm
Package 1 Width	160 mm
Package 1 Length	110 mm
Package 1 Weight	9.45 kg

Contractual warranty

Warranty 1 year repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >





Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration	
Eu Rohs Directive	Compliant EU RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Circularity Profile	End of Life Information	