Product datasheet

Specifications





APC Smart-UPS, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartSlot, AVR, LCD

SMT1000I

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead Time	Usually Ships within 2 Weeks
Main	
Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	700 W
Rated Power In Va	1000 VA
Input Connection Type	IEC 320 C14
Output Connection Type	8 IEC 320 C13 2 IEC Jumpers
Battery Type	Lead-acid battery
Provided Equipment	USB cable Documentation CD Installation guide Smart UPS signalling RS-232 cable

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
Extended Runtime	0
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	3 h
Number Of Battery Replacement Quantity	1
Battery Life	35 year(s)
Replacement Battery	RBC6 ☐
Battery Charger Power	88 W rated



General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Redundant	No

Physical

Colour	Black
Height	21.9 cm
Width	17.1 cm
Depth	43.9 cm
Net Weight	18.86 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Input Voltage Limits	151302 V adjustable 160286 V
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic Distortion	Less than 5 % at full load
Maximum Configurable Power In Va	1000 VA
Maximum Configurable Power In W	700 W
Ups Type	Line interactive
Wave Type	Sine wave
Output Frequency	4753 Hz for 50 Hz nominal sync to mains

Conformance

Product Certifications	CE EAC RCM VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic Level	41 dBA
Heat Dissipation	100 Btu/h
Operating Altitude	010000 ft
Ambient Air Temperature For	040 °C

Ambient Air Temperature For Storage	-1545 °C
Storage Altitude	0.0015240.00 m
Relative Humidity	095 %
Storage Relative Humidity	n 95 %

Communications & Management

Control Panel	Multifunction LCD status and control console
Emergency Power Off	Optional
Free Slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rate	459 J
Noise Suppression	Full time multi-pole noise filtering: 0.3% IEEE surge let-through: zero clamping response time: meets UL 1449

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	37.6 cm
Package 1 Width	32.8 cm
Package 1 Length	59.5 cm
Package 1 Weight	22.77 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	9
Package 2 Height	124 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	419.5 kg
Scc14	731304268673

Contractual warranty

Warranty 3 years repair or replace (excluding battery) and 2 years for battery

Apr 23, 2024



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product



Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

Reach Regulation REACh Declaration Eu Rohs Directive Compliant with Exemptions **Environmental Disclosure** Product Environmental Profile Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins **Circularity Profile** End of Life Information