Product datasheet

Specifications





APC Back-UPS, 2200VA, Tower, 230V, 4x CEE 7/5 French Schuko outlets, AVR

BX2200MI-FR

Overview

Lead Time Usually in Stock

Main

Mani	
Main Input Voltage	230 V
Rated Power In W	1200 W
Rated Power In Va	2200 VA
Input Connection Type	French/Belgian
Output Connection Type	4 French
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery Recharge Time	8 h
Battery Voltage	24 V
Battery Capacity	9.0 Ah
Battery Life	35 year(s)
Replacement Battery	APCRBC177 ☐
Battery Graph Comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended Runtime	0

General

Provided Equipment	user manual	
Number Of Power Module Filled Slots	0	
Redundant	No	

Physical

Colour	Black
Height	19 cm

Width	14 cm
Depth	39 cm
Net Weight	12.3 kg
Mounting Preference	No preference
Mounting Mode Not rack-mountable	

Input

Network Frequency	50/60 Hz +/- 5 Hz auto-sensing	
Plug Standard	French/Belgian	
Input Voltage Limits	140300 V	
Input Power Factor At Full Load	0.54	

Output

Maximum Configurable Power In W	1200 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Full Load Runtime	00:01:00 1200 W
Half Load Runtime	00:08:30 600 W
Maximum Configurable Power In Va	2200 VA
Transfer Time	6 ms typical : 10 ms maximum

Conformance

Product Certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment Protection Policy	Lifetime : 50000 euros

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 % non-condensing
Operating Altitude	03000 m
Ambient Air Temperature For Storage	-1540 °C
Storage Relative Humidity	095 % non-condensing
Storage Altitude	03000 m
Acoustic Level	40 dBA
Ip Degree Of Protection	IP20

Communications & Management

Control Panel LED Status display with on line : on battery

Surge Protection and Filtering

Surge Energy Rate 273

Packing Units

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	23.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	13.6 kg
Scc14	10731304420511

Contractual warranty

26 Apr 2024

Warranty 2 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >





Transparency RoHS/REACh

Well-being performance

	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information