Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# **Product datasheet**

Specification





APC Smart-UPS X, Line Interactive, 1500VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, SmartSlot, Extended runtime

SMX1500RMI2U

#### Overview

| Presentation           | Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices. |
|------------------------|---|
| Lead Time              | Usually Ships within 2 Weeks  |
| Main                   |   |
| Main Input Voltage     | 230 V   |
| Main Output Voltage    | 230 V   |
| Rated Power In W       | 1200 W  |
| Rated Power In Va      | 1500 VA   |
| Input Connection Type  | IEC 320 C14   |
| Output Connection Type | 8 IEC 320 C13<br>2 IEC Jumpers  |
| Number Of Rack Unit    | 2U  |
| Cable Length           | 1.83 m  |
| Number Of Cables       | 1   |
| Battery Type           | Lead-acid battery   |
| Provided Equipment     | CD with software Documentation CD Installation guide Rack mounting support rails Removable support feet Smart UPS signalling RS-232 cable USB cable                               |

### **Batteries & Runtime**

| Run Time                               | View Runtime Graph ☐    |
|--|-------------------------|
| Efficiency                             | View Efficiency Graph ☐ |
| Extended Runtime                       | 0                       |
| Number Of Battery Filled Slots         | 0                       |
| Number Of Battery Free Slots           | 0                       |
| Battery Recharge Time                  | 3 h                     |
| Number Of Battery Replacement Quantity | 1                       |
| Battery Life                           | 35 year(s)              |
| Replacement Battery                    | APCRBC115 ☐             |

### General

| Number Of Power Module Filled Slots | 0            |
|-------------------------------------|--------------|
| Number Of Power Module Free Slots   | 0            |
| Product Web Sub-Family              | Extended run |
| Redundant                           | No           |

# **Physical**

| Colour              | Black        |
|---------------------|--------------|
| Height              | 8.9 cm       |
| Width               | 43.2 cm      |
| Depth               | 49 cm        |
| Net Weight          | 24.82 kg     |
| Mounting Preference | Lower        |
| Mounting Mode       | Rack-mounted |
| Two Post Mountable  | 0            |
| Usb Compatible      | Yes          |

# Input

| Switching Current Capacity | 10 A                            |
|----------------------------|---------------------------------|
| Input Voltage Limits       | 151302 V adjustable<br>160286 V |
| Network Frequency          | 50/60 Hz +/- 3 Hz auto-sensing  |

# Output

| Harmonic Distortion              | Less than 5 %                   |
|----------------------------------|---------------------------------|
| Maximum Configurable Power In Va | 1500 VA                         |
| Maximum Configurable Power In W  | 1200 W                          |
| Ups Type                         | Line interactive                |
| Wave Type                        | Sine wave                       |
| Output Frequency                 | 50/60 Hz +/- 3 Hz sync to mains |

## Conformance

| Product Certifications | CE<br>RCM<br>VDE<br>EAC                                     |
|------------------------|---|
| Standards              | EN/IEC 62040-1:2019/A11:2021<br>EN/IEC 62040-2:2006/AC:2006 |
|                        | EN/IEC 62040-2:2018   |

## **Environmental**

| Acoustic Level   | 40 dBA    |
|------------------|-----------|
| Heat Dissipation | 133 Btu/h |

| Operating Altitude                    | 010000 ft      |
|---------------------------------------|----------------|
| Ambient Air Temperature For Operation | 045 °C         |
| Ambient Air Temperature For Storage   | -1545 °C       |
| Storage Altitude                      | 0.0015240.00 m |
| Relative Humidity                     | 095 %          |
| Storage Relative Humidity             | 095 %          |

## **Communications & Management**

| Control Panel       | Multifunction LCD status and control console                                     |
|---------------------|--|
| Emergency Power Off | Yes  |
| Free Slots          | 1  |
| Alarm               | Alarm when on battery : distinctive low battery alarm : overload continuous tone |

## **Surge Protection and Filtering**

| Surge Energy Rate | 645 J  |
|-------------------|--|
| Noise Suppression | Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449 |

## **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 24.6 cm |
| Package 1 Width              | 58.9 cm |
| Package 1 Length             | 62 cm   |
| Package 1 Weight             | 30 kg   |
| Unit Type Of Package 2       | PAL     |
| Number Of Units In Package 2 | 16      |
| Package 2 Height             | 133 cm  |
| Package 2 Width              | 100 cm  |
| Package 2 Length             | 120 cm  |
| Package 2 Weight             | 524 kg  |

## **Contractual warranty**

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

### Resource performance

Energy Efficient Product



### Well-being performance

Mercury Free

Rohs Exemption Information Yes

#### **Certifications & Standards**

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

Product Environmental Profile

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

End of Life Information