# **Product datasheet**

Specifications



# rack PDU - basic - 1U - 16A 208 230V - (12)C13



AP9565

## **Overview**

Presentation	Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (12)C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
Lead Time	Usually in Stock

## Main

Colour	Black
Pdu Type	Basic
Cord Length	2.50 m
Number Of Cables	1
Provided Equipment	Installation guide Rack mounting brackets

## Complementary

Input Voltage	200 V 208 V 230 V
Height	4.4 cm
Width	44.7 cm
Output Voltage	208 V 230 V
Depth	5.7 cm
Net Weight	2.05 kg
Mounting Location	Front Rear
Mounting Preference	No preference
Input Plug Type	IEC 60320 C20
Mounting Mode	Rack-mounted
Rack Units	1U
Mounting Position	Horizontal
Input Current Limits	16 A
Load Capacity	3680 VA
Network Frequency	50/60 Hz
Total Number Of Outlets	12 IEC 60320 C13

## **Environment**

Product Certifications	cUL listed CE Queensland Australia UL listed VDE
Standards	UL 60950
Ambient Air Temperature For Operation	045 °C
Relative Humidity	095 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	095 %
Storage Altitude	0.0015240.00 m

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7 cm
Package 1 Width	46.4 cm
Package 1 Length	22.9 cm
Package 1 Weight	3.632 kg

# **Contractual warranty**

Warranty 2 years repair or replace



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

### Resource performance

Energy Efficient Product



Take-Back Program Available

### Well-being performance



Lead Free

#### **Certifications & Standards**

Reach Regulation

Eu Rohs Directive

Compliant

EU RoHS Declaration

Environmental Disclosure

Product Environmental Profile

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

End of Life Information