

Product datasheet

Specifications



Smart-UPS VT 10kVA 400V w/2 battery to 4 - Start-up 5x8 - int maint Bypass - //

SUVTP10KH2B4S

! Discontinued on: 5 Jul 2021

! End-of-service on: 18 Oct 2023

! Discontinued

Overview

Lead Time Usually Ships within 2 Weeks

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated Power In W	8000 W
Rated Power In Va	10000 VA
Output Connector Type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1
Connections - Terminals	1 screw terminals
Provided Equipment	Battery modules ship installed CD with software Network management card Power modules ship installed User manual Bolt down brackets Installation guide Start up included

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery Type	VRLA
Number Of Battery Filled Slots	2
Number Of Battery Free Slots	2
Battery Recharge Time	5 h
Number Of Battery Replacement Quantity	2
Battery Voltage	+/- 192 V (split battery referenced to neutral)
Discharge Battery Voltage	+/- 154 V
Battery Charger Power	995 W rated

Battery Life	3...5 year(s)
Battery Graph Comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.8 output.
Extended Runtime	1

General

Ups Type	Double conversion online
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Black
Height	149 cm
Width	52.3 cm
Depth	84.2 cm
Net Weight	415 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	47...70 Hz auto-sensing
Number Of Input Connectors	1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	304...477 V
Maximum Input Current	14 A
Switching Current Capacity	20 A
Input Power Factor At Full Load	0.98

Output

Maximum Configurable Power In Va	10000 VA
Maximum Configurable Power In W	8000 W
Output Frequency	47...53 Hz for 50 Hz nominal sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Wave Type	Sine wave
Harmonic Distortion	Less than 5 % at full load
Maximum Output Current	16 A
Crest Factor	3 : 1
Bypass Type	Built-in maintenance bypass Built-in static bypass
Additional Information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage

Conformance

Product Certifications	C-Tick CE RCM
------------------------	---------------------

Environmental

Ambient Air Temperature For Operation	0...40 °C
---------------------------------------	-----------

Relative Humidity	0...95 %
-------------------	----------

Operating Altitude	0...3333 ft
--------------------	-------------

Ambient Air Temperature For Storage	-50...40 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage Altitude	0.00...15240.00 m
------------------	-------------------

Acoustic Level	64 dBA
----------------	--------

Heat Dissipation	1774 Btu/h
------------------	------------

Ip Degree Of Protection	IP20
-------------------------	------

Communications & Management

Free Slots	0
------------	---

Preinstalled Device	Network management card 2 with environmental monitoring
---------------------	---

Emergency Power Off	Yes
---------------------	-----

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	164.3 cm
------------------	----------

Package 1 Width	106.2 cm
-----------------	----------

Package 1 Length	65 cm
------------------	-------

Package 1 Weight	445.91 kg
------------------	-----------

Contractual warranty

Warranty	1 year repair or replace, Start-Up Service
----------	--

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
