Product data sheet

Specifications





APC Back-UPS CS 650VA, 230V, 4 IEC outlets (1 surge)

BK650-AS

Overview

Lead Time	Usually in Stock
Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	400 W
Rated Power In Va	650 VA
Product Or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
Output Connection Type	3 IEC 60320 C13 1 IEC 60320 C13 surge
Cable Length	1.83 m
Number Of Cables	2
Battery Type	Lead-acid battery
Provided Equipment	CD with software Documentation CD 1 x detachable 1.2 m IEC power cord 1 x detachable 1.8 m IEC power cord Telephone cable USB cable

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	12 W rated
Battery Power In Vah	95 VAh runtime
Battery Life	46 year(s)
Replacement Battery	RBC17 ☐
Extended Runtime	0

Warranty card



General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

•	
Colour	Beige
Height	16.5 cm
Width	9.1 cm
Depth	28.4 cm
Net Weight	6.04 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	160282 V adjustable 180260 V

Output

Maximum Configurable Power In W	400 W
Ups Type	Standby
Wave Type	Stepped approximation to a sinewave
Maximum Configurable Power In Va	650 VA

Conformance

A-Tick C-Tick
CE

GOST
NEMKO
EN/IEC 62040-1:2019/A11:2021
EN/IEC 62040-2:2006/AC:2006
EN/IEC 62040-2:2018
Lifetime: \$100000
Lifetime: 50000 GBP

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	595 %
Operating Altitude	030000 ft
Ambient Air Temperature For Storage	-1545 °C

Storage Relative Humidity	595 %
Storage Altitude	0.004572.00 m
Acoustic Level	45 dBA
Heat Dissipation	0 Btu/h

Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rate 320 J

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	49.4 cm
Package 1 Width	41.5 cm
Package 1 Length	18.5 cm
Package 1 Weight	7.32 kg
Scc14	10731304224430

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information Y

Yes

Certifications & Standards

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information