Product data sheet

Specifications





Usually in Stock

IEC 60320 C13

6 IEC 60320 C13 2 IEC 60320 C13 surge

APC Back-UPS Pro, 1600VA/ 960W, Tower, 230V, 8x IEC C13 outlets, AVR, LCD, User Replaceable Battery

BR1600MI

Overview

Lead Time

Main	
IVIAIII	
Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	960 W
Rated Power In Va	1600 VA
Product Or Component Type	Uninterruptible power supply (UPS)

Battery Type Lead-acid battery

Batteries & Runtime

Input Connection Type

Output Connection Type

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	16 h
Number Of Battery Replacement Quantity	1
Battery Voltage	24 V
Battery Capacity	9.0 Ah
Battery Charger Power	11 W rated
Battery Life	35 year(s)
Replacement Battery	APCRBC166 ☐
Extended Runtime	0

General

Provided Equipment	user manual USB cable
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0

Apr 23, 2024 Life Is On

Redundant	No

Physical

Colour	Black
Height	10 cm
Width	25 cm
Depth	38.2 cm
Net Weight	10.9 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	176294 V
Maximum Input Current	10 A
Switching Current Capacity	10 A

Output

Maximum Configurable Power In W	960 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Maximum Configurable Power In Va	1600 VA

Conformance

Product Certifications	A-Tick C-Tick CE EAC
	RCM TISI
Marking	GS Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 % non-condensing
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-1545 °C
Storage Relative Humidity	095 % non-condensing
Storage Altitude	0.0015240.00 m
Acoustic Level	45 dBA

Heat Dissipation 21.5 Btu/h

Communications & Management

Control Panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rate	509 J
Noise Suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	33 cm
Package 1 Width	22.5 cm
Package 1 Length	48.5 cm
Package 1 Weight	11.65 kg
Scc14	10731304346910

Contractual warranty

Warranty

2 years repair or replace, 3 years repair or replace for European Union countries



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product



Take-Back Program Available

Well-being performance

Rohs Exemption Information

Certifications & Standards

Reach Regulation REACh Declaration Eu Rohs Directive Compliant with Exemptions **China Rohs Regulation** China RoHS declaration Product out of China RoHS scope. Substance declaration for your information **Environmental Disclosure Product Environmental Profile Circularity Profile** End of Life Information