## **Product datasheet**

Specifications





APC Smart-UPS VT 15kVA 400V w/3 Batt Mod Exp to 4, Start-Up 5X8, Int Maint Bypass, Parallel Capable

SUVTP15KH3B4S

- ! Discontinued on: 5 Jul 2021
- ! End-of-service on: 18 Oct 2023

#### **Overview**

Lead Time

Main Main Input Voltage 400 V 3 phases Other Input Voltage 380 V 415 V Main Output Voltage 400 V 3 phases Other Output Voltage 380 V 415 V Rated Power In W 12000 W Rated Power In Va 15000 VA **Output Connector Type** Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1 **Connections - Terminals** 1 screw terminals **Provided Equipment** Battery modules ship installed

Usually Ships within 2 Weeks

CD with software Network management card Power modules ship installed

User manual Bolt down brackets Installation guide Start up included

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery Type	VRLA
Number Of Battery Filled Slots	3
Number Of Battery Free Slots	1
Battery Recharge Time	5 h
Number Of Battery Replacement Quantity	3
Battery Voltage	+/- 192 V (split battery referenced to neutral)
Discharge Battery Voltage	+/- 154 V

Battery Charger Power	1482 W rated
Battery Life	35 year(s)
Battery Graph Comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.8 output.
Extended Runtime	1

## General

Ups Type	Double conversion online
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

# **Physical**

•	
Colour	Black
Height	149 cm
Width	52.3 cm
Depth	84.2 cm
Net Weight	506.82 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

# Input

Network Frequency	4070 Hz auto-sensing
Number Of Input Connectors	1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	304477 V
Maximum Input Current	21 A
Switching Current Capacity	35 A
Input Power Factor At Full Load	0.98

# Output

Maximum Configurable Power In Va	15000 VA
Maximum Configurable Power In W	12000 W
Output Frequency	4753 Hz for 50 Hz nominal sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Wave Type	Sine wave
Harmonic Distortion	Less than 5 % at full load
Maximum Output Current	24 A
Crest Factor	3:1
Bypass Type	Built-in maintenance bypass Built-in static bypass

Additional Information Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage

#### **Conformance**

Product Certifications C-Tick
CE
RCM

#### **Environmental**

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 %
Operating Altitude	03333 ft
Ambient Air Temperature For Storage	-5040 °C
Storage Relative Humidity	095 %
Storage Altitude	0.0015240.00 m
Acoustic Level	64 dBA
Heat Dissipation	2170 Btu/h
Ip Degree Of Protection	IP20

## **Communications & Management**

Free Slots	0
Preinstalled Device	Network management card 2 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off	Yes

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	164.3 cm
Package 1 Width	65 cm
Package 1 Length	106.2 cm
Package 1 Weight	537.73 kg

## **Contractual warranty**

Warranty 1 year repair or replace, Start-Up Service



**Green Premium**<sup>TM</sup> label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Learn more about Green Premium >







Take-back Transparency RoHS/REACh

#### Resource performance



Take-Back Program Available

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information