Product data sheet

Specifications

APC Smart-UPS On-Line, 10kVA/ 10kW, Tower, 230V/400V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/O rail kit

SRT10KXLI

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead Time	Usually in Stock

Main

Main Input Voltage	230 V 400 V 3 phase
Other Input Voltage	220 V 240 V 380 V 415 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Kw Rating	10000 W
Rated Power In Va	10000 VA
Output Connection Type	6 IEC 60320 C13 3 IEC Jumpers 4 IEC 60320 C19
Output Connector Type	Hard Wire 3-wire (H N + E) 1
Provided Equipment	CD with software Documentation CD Installation guide Temperature Probe USB cable Warranty card Web/SNMP Management Card

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery Type	Lead-Acid battery
Included Battery Modules	0
Typical Recharge Time	1.5 h
Rbc Quantity	2
Battery Voltage	+/-192 V (split battery referenced to neutral)
Battery Charge Power (Watts)	876 W rated
Battery Life	3…5 year(s)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Replacement Battery	APCRBC140 SRT192BP2US SRT192RMBPUS
Extendable Run Time	1

General

Topology	Double Conversion Online
Product Web Sub-Family	High density
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	10.35 in (26.3 cm)
Depth	28.15 in (71.5 cm)
Net Weight	246.52 lb(US) (111.82 kg)
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Rack-mounted with kit
Two Post Mountable	0
Usb Compatible	Yes

Input

Input Frequency	40 - 70 Hz auto-sensing
Number Of Input Connectors	1 Hard Wire 3-wire (1PH+N+G) 1 Hard Wire 5-wire (3PH + N + G)
Efficiency At Full Load	100...275 V adjustable (half load) 173...476 V adjustable (half load)

Output

Maximum Configurable Power In Va	10000 VA
Max Configurable Power (Watts)	10000 W
Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz sync to mains
Wave Type	Sine wave
Harmonic Distortion	Less than 2%
Crest Factor	3 : 1
Bypass Type	Internal Bypass (Automatic and Manual)

Conformance

Product Certifications	CE EAC IRAM RCM VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	32…104 °F (0…40 °C)
Relative Humidity	0…95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	5…113 °F (-15…45 °C)
Storage Relative Humidity	0…95 % non-condensing
Storage Altitude	0…50000 ft (0.00…15240.00 m)
Acoustic Level	55 dBA
Heat Dissipation	1947 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Free Slots	1
Pre-Installed Smartslot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (Epo)	Yes

Surge Protection and Filtering

Surge Energy Rating	480 J

Ordering and shipping details

Gtin	731304304272
Country Of Origin	PH

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	18.15 in (46.1 cm)
Package 1 Width	23.62 in (60 cm)
Package 1 Length	39.37 in (100 cm)
Package 1 Weight	279.00 lb(US) (126.554 kg)

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Learn more about Green Premium >

Energy Efficient | Take-back | Transparency | RoHS/REACh

Resource performance

- Energy Efficient Product
- Take-Back Program Available

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov